

双钢轮振动压路机

Double Drum Vibratory Rollers



本系列属小型两轮串联振动压路机，适用于各种道路修补和高速公路路肩、人行道、体育场和花园草坪的碾压工作，并适合于压实管道和排水管沟槽等场地的压实作业。

The tandem vibratory rollers are small-size tandem vibratory roller, applied to mending and maintaining various roads, expressway shoulder, side walk, parking area, sports ground and garden lawn. They are especially suited for compaction of narrow areas as pipeline channel and drainage trench etc.

8035L/8045L主要特点

- 采用常柴ZN385Q/ZN390Q 柴油机起动性能好；
- 齿轮侧传动后轮驱动，前轮振动；
- 前、后机身铰接，助力转向；叉脚式侧板，压边高度大于600mm；
- 变速箱拥有日本技术，排挡轻松自如；三挡变速压实效果好，转场快捷；
- 可选配拖板车；
- 两项国家专利。
- Adopt ZN385Q/ZN390Q engine manufactured by Changchai Co., Ltd. with good starting performance.
- The rear-drum drive with side gear transmission and vibration in the front drum.
- The front and rear frame articulated and power steering. Fork-type drum brackets with more than 600mm drum-side clearance.
- The gearbox uses Japanese technology with easy gearshift; And three travel speeds possess good compaction and fast transportation.
- Platform trailer as option.
- Two the state patents.

80255L 主要特点

- 该机采用机械行走、液压振动、液压铰接转向；操作方便灵活，具有可靠的性能和优良的性价比；
- 选配优质高效的常柴发动机，功率储备大、性能可靠、质量稳定、油耗低、使用维修方便；
- 整机结构紧凑，体积小，造型美观大方，可用于狭窄场地压实作业；
- 前后压轮均有刮泥和洒水装置，利于提高施工质量；
- 遮阳篷为伞篷或玻璃钢篷；
- 可选配拖板车。
- Mechanical travel drive, hydraulic vibration and steering with reliable performance, easy operation and good function/worth ratio.
- Reliable and powerful Changchai engine with large power reservation, reliable performance, stable quality, low oil consumption and convenient in operation and maintenance.
- Compact design of small size and beautiful appearance, suited for compaction of the narrow areas.
- Scrapers and sprinkling devices on all drums for improving quality of construction.
- Driver's canopy is made from pergola adopt umbrella clothes or fiber reinforced plastics.
- Platform trailer as option.

主要技术参数

型号			8035L	JCC204	8045L	YZC215	80255L
工作质量	Operating mass	kg	3000		4000		2500
静线载荷(前/后)	static linear load(F/R)	N/cm	120/153		150/184		120/158
振幅	Vibration amplitude	mm	0.5		0.5		0.5
振动频率	Vibration frequency	Hz	50		50		50
激振力	Centrifugal force	kN	32		39		25
最高行走速度	Max. travel speed	km/h	7.8		8		5.6
爬坡能力	Gradeability	%	20		20		20
转弯半径	Turning radius	mm	4500		6000		4300
振动轮宽度×直径	Drum width	mm	1100×780		1200×900		900×749
轴距	Wheelbase	mm	2050		2200		1980
最小离地间隙	Ground clearance	mm	300		300		220
柴油机型号	Diesel model		385/390		CHANGCHAI ZN390Q		CHANGCHAI CN380
柴油机功率	Diesel power	kW	21/22		22		14.7
外形尺寸	Overall dimensions	mm	2880×1280×2650		3180×1420×2650		2765×1156×2550

本产品在不断改进，规格、说明及外观如有变动，恕不另行通知，请谅。

Since the product is improved continuously, the specification and instruction are subject to change without separate notice.