

# 全液压轮胎压路机

## Hydraulic Pneumatic Tire Rollers



本系列是光面轮胎压路机，主要适合于路面工程中各种粘性和非粘性材料，如沙土，碎石，稳定土、沥青混凝土，干硬性混凝土等材料的压实，尤其适宜于高等级公路的沥青面层的最终处理，是建设高等级公路、机场、市政工程及工业场地的高性能压实设备。

Pneumatic smooth-tire rollers is suitable for compaction of various cohesive and non-cohesive materials such as sandy soil, crushed stone, stabilized soils, bituminous concrete and rolling cement concrete (RCC) on road surface construction, especially for final compaction of asphalt surface on high-class highway, which is super quality compaction equipments for high-class highway, airport, municipal road and industrial ground.

### 主要特点

- 著名品牌发动机，动力强劲有力，可适应于各种恶劣工况；
- 液压行走传动，进口液压柱塞泵马达，两挡无级变速，减少对路面震动冲击；
- 通过加水或湿沙可调节压路机配重和接地比压，调节方便范围大；
- 电控动力洒水系统，玻璃钢水箱，多级水过滤器，安全可靠；
- 整机结构紧凑，造型美观；
- 宽敞封闭驾驶室设有通风装置和空调（选择配置）。
- Powerful Famous brand diesel engine for various working conditions.
- Hydrostatic travel drive with imported hydraulic pump and motor at two-range infinitely variable speeds results in less shock to road surface.
- Operating weight and ground contact pressure can be adjusted by filling water or wet sand with greater adjusting scope.
- Power sprinkler system with corrosion free materials and reinforced polyethylene water tank and multi-stage water filters for reliable operation.
- Unique, beautiful and compact appearance design .
- Spacious and closed operator's cab with ventilating and air conditioning devices (optional).

### 主要技术参数

型号			8352L	8302L	8262L	8162GL
最大工作质量	Max. operating mass	kg	35000	30000	26000	16000
最小工作质量	Min. operating mass	kg	30000	25000	16000	9000
最高前进速度	Max. travel speed	km/h	11.5	13	15	15
轮胎数量	Tire number		5+6	5+6	5+6	4+5
平均接地比压	Tire contact pressure	kPa	400 ~ 530	307-460	250-420	150 ~ 300
最小转弯半径	Turning radius	mm	9000	9000	8300	7500
碾压宽度	Rolling width	mm	3065	2890	2790	2290
轮胎重叠宽度	Wheel overlap	mm	50	50	50	50
爬坡能力	Gradeability	%	20	20	20	20
柴油机型号	Diesel model		SC8D200	SC8D180	Cummins6BT5.9	Cummins4BTA3.9
柴油机功率	Diesel power	kW	147	132	110	95
柴油机转速	Diesel speed	r/min.	2300	2000	2200	2400
外形尺寸（驾驶室）	Overall dimensions(with cabin)	mm	5524 × 3065 × 3270	5230 × 2890 × 3210	4874 × 2790 × 3100	4770 × 2290 × 3162
外形尺寸（遮阳蓬）	Overall dimensions(with canopy)	mm				4770 × 2290 × 3192

因产品在不断改进，规格、说明及外观如有变动，恕不另行通知，请谅。

Since the product is improved continuously, The specification and instruction are subject to change without separate notice.